

Please Call for Updated Pricing!



Titebond® Carpenters Glue

Titebond® Carpenters Glue is a professional-strength formula designed for general woodworking applications. This glue is intended for interior use, develops bonds stronger than wood itself, offers strong initial tack, sands easily and is unaffected by finishes. Titebond Carpenters Glue bonds both hardwoods and softwoods, as well as particleboard, leather, cloth and most other porous materials. It is non-toxic, easy to use and cleans up with water.



Titebond® II Extend Wood Glue

Titebond® II Extend Wood Glue combines weatherproof performance (ANSI Type II water-resistance) with a slower speed of set. It is ideal for exterior applications that involve more complex assemblies. It also provides a translucent glue line, offers excellent sandability and is unaffected by finishes. It offers superior performance on all common wood species, particleboard, MDF, plywood and other porous materials.



Titebond® GREENchoice™ Fast Grab FRP Adhesive

Titebond® GREENchoice™ Fast Grab FRP adhesive is the #1 recommended adhesive in the FRP industry. Fast Grab is a high-quality, VOC-compliant adhesive specifically formulated for the installation of FRP (fiber-reinforced plastic) panels. Its fast grab and bonding power greatly reduce the need for extended bracing.

Fast Grab is environmentally superior and unlike solvent-based adhesives, it is nonflammable, emits no harmful fumes and cleans up with water.



Titebond® GREENchoice™ Advanced Polymer Panel Adhesive

Titebond® GREENchoice™ Advanced Polymer Panel Adhesive is a high performance, professional strength advanced polymer adhesive specifically formulated to be used for most types of paneling installations. It has fast grab, a rapid cure rate, trowels easily, is moisture, mold and mildew resistant, and contains no water. Titebond® GREENchoice Advanced Polymer Panel's formula is VOC-compliant, nonflammable, and environmentally safe — emitting no harmful fumes and promoting healthy living and working environments.



Titebond® All Weather Subfloor Adhesive

This adhesive is designed for interior and exterior subfloor installations. Its premium formulation allows for cold-weather extrusion and is designed for bonding particleboard, OSB, engineered lumber and wet, frozen and treated lumber. Provides professional strength and remains permanently flexible.

Performance

- All-weather durability
- Excellent bond strength
- Eliminates squeaks
- Reduces nailing
- Ideal for wet & frozen lumber
- Extrudes 0° - 100°F

Exceeds Specifications

- APA AFG-01
- ASTM D3498
- ASTM C557



Titebond® Contractor Grade Subfloor Adhesive

Titebond® Contractor Grade Subfloor Adhesive is a '4 Seasons' solvent free formula. It extrudes down to 20°F and up to 120°F, reduces squeaky floors, bridges gaps, minimizes use of fasteners and provides superior adhesion in adverse weather conditions. This adhesive meets LEED/NAHB VOC requirements and is ideal for use on wafer board, particleboard, engineered lumber, paneling and wet, frozen and treated lumber.

Exceeds Specifications

- APA AFG-01
- ASTM C557

Please Call for Updated Pricing!

Titebond®

THE PRO'S ADVANTAGE™



Titebond® III Ultimate Wood Glue

An advanced proprietary technology that offers the best possible performance in woodworking glues. This waterproof formula passes the ANSI/HPVA Type I water-resistance specification and offers superior bond strength, longer open assembly time along with lower application temperature (chalk point). Titebond III Ultimate Wood Glue is non-toxic, solvent free and cleans up with water – safer to use than traditional waterproof wood glues. It provides strong initial tack, sands easily without softening and is FDA approved for indirect food contact (cutting boards). Titebond III is the ultimate in wood glues – ideal for both interior and exterior applications.

Titebond® II Premium Wood Glue

The first leading brand, one-part PVA wood glue to pass the ANSI/HPVA Type II water-resistance specification. Titebond II Premium Wood Glue is ideal for interior or exterior woodworking projects, including outdoor furniture, birdhouses, planters, mailboxes and picnic tables. It offers strong initial tack, outstanding bond strength, fast speed of set and excellent sandability. Titebond II Premium Wood Glue is FDA approved for indirect food contact (cutting boards) and is ideal for radio-frequency (R-F) gluing systems. It is non-toxic, solvent free and cleans up with water.



Titebond® Original Wood Glue

The industry standard for general woodworking, this original aliphatic-resin glue has been the professional's choice for over 50 years. It provides strong initial tack and fast speed of set to reduce clamp time. Titebond Original Wood Glue develops bonds stronger than the wood itself, offers excellent sandability and is unaffected by finishes. It provides superior resistance to heat, solvent and mildew, and is ideal for hardwoods, softwoods and most other porous materials. It is easy to use, non-toxic, solvent free and cleans up with water.

TECHNICAL INFORMATION

PRODUCTS	TYPE	STRENGTH	CHALK TEMP	SHELF LIFE	DRIED FILM	VOC	OPEN/TOTAL ASSEMBLY TIME
Titebond III Ultimate	Proprietary Polymer	4,000 psi	45°F	2 years	Light Brown	9 g/L	8-10/20-25 minutes
Titebond II Premium	Cross-linking PVA	3,750 psi	55°F	2 years	Yellow	3 g/L	3-5/10-15 minutes
Titebond Original	Aliphatic Resin	3,600 psi	50°F	2 years	Yellow	10.7 g/L	4-6/10-15 minutes